

## ASTM F891 SCH 40 FOAM CORE MANUFACTURER'S CERTIFICATION

This is to certify the pipe manufactured by Sanderson Pipe Corporation meets or exceeds the applicable engineering standards listed below for ASTM F891 Schedule 40 coextruded cellular core drain, waste, vent pipe.

### Materials

Comply with ASTM D4396 cell classification 11432.

### Dimensions/Testing

All pipe meets or exceeds the performance requirements listed in the current version of ASTM F891.

### Markings on the Pipe

Identification of nominal pipe size, plastic pipe material code, schedule size, ASTM designation F891, the labeling "COEXTRUDED CELLULAR CORE PVC PIPE", manufacturer's name and code, the National Sanitation Foundation seal

for drain, waste, vent (NSF-dwv). Additional labeling on the pipe will include "NOT FOR PRESSURE".

### Color

Foam Core pipe is white.

### Length

Manufactured in 10' or 20' over-all lengths.

### Assembly

Refer to standard ASTM D2855.

Pipe Size	Outside Diameter	Minimum Wall
1 ½"	1.900"	0.145"
2"	2.375"	0.154"
3"	3.500"	0.216"
4"	4.500"	0.237"
6"	6.625"	0.280"



## Loading Chart | Foam Core

Pipe Size	Pipe Length	Pieces per Pallet	Feet per Pallet	Pallets per Truck	Feet per Truck
1 ½"	10'	221	2,210'	48	106,080'
	20'	221	4,420'	24	106,080'
2"	10'	140	1,400'	40	56,000'
	20'	140	2,800'	20	56,000'
3"	10'	63	630'	48	30,240'
	20'	63	1,260'	24	30,240'
4"	10'	57	570'	32	18,240'
	20'	57	1,140'	16	18,240'
6"	10'	26	260'	32	8,320'
	20'	26	520'	16	8,320'

